

Gree Gama Bora A4 Silver



Model			GWH09AAA-K6DNA4A	GWH12AAB-K6DNA4B	GWH18AAD-K6DNA4E	GWH24AAD-K6DNA4B
Funcție		U.M.	Racire / Incalzire	Racire / Incalzire	Racire / Incalzire	Racire / Incalzire
Capacitate	Racire min/nom/max	BTU/h	1706/8530/11089	3071/10919/12283	3412/15700/18084	6100/21000/23500
	Incalzire min/nom/max	BTU/h	1706/9553/11942	3071/11601/13648	2388/17742/19278	4400/22000/23998
SEER/SCOP		W/W	6.5 / 4	6.1 / 4	6.4 / 4	6.8 / 4
Clasa de energie	Racire / Incalzire		A++ / A+	A++ / A+	A++ / A+	A++ / A+
Alimentare		Ph-V-Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Putere electrica consumata	Racire min/nom/max	W	150/720/1300	220/991/1300	420/1355/1800	450/1827/2200
	Incalzire min/nom/max	W	140/750/1500	220/916/1500	420/1340/1900	450/1912/2300
Curent nominal	Racire	A	3.2	4.4	5.9	7.6
	Incalzire	A	3.2	4	5.8	7.6
Dezumidificare		L/h	0.60	1.4	1.8	1.8
Debit de aer	(SH/H/M/L)	(m³/h)	500/470/390/250	590/520/480/400/350/320/280	850/800/700/550	900/800/700/600/500/400/350
Unitate interioara						
Nivel de Presiune Acustica	(SH/H/M/L)	dB(A)	38/36/32/22	41/37/33/26	44/42/38/31	48/45/42/37/32/30/26
Nivel de putere acustica	(SH/H/M/L)	dB(A)	55/48/44/34	56/49/45/38	54/52/48/41	60/57/54/49/44/42/38
Dimensiune neta	Lxlxh	mm	698×185×250	773×185×250	970×225×300	970×225×300
Dimensiune bruta	Lxlxh	mm	745×255×322	822×255×322	1020×295×369	1020×295×369
Greutate neta/ Greutate bruta		kg	7.5 / 8.5	8 / 9.5	13.5/16	13/15.5
Unitate exterioara						
Nivel de Presiune Acustica dB(A)		dB(A)	51	51	53	57
Nivel de putere acustica		dB(A)	62	64	63	65
Domeniu temperatura exterioara functionare	Racire (Min-Max)	°C	(-15 ~ 43)	(-15 ~ 43)	(-15 ~ 43)	(-15 ~ 43)
	Incalzire (Min-Max)	°C	(-15~ 24)	(-15~ 24)	(-15~ 24)	(-15~ 24)
Traseu frigorific	Lungime maxima	m	15	15	25	25
	Diferenta maxima de nivel	m	10	10	10	10
Dimensiune neta	Lxlxh	mm	732×330×550	732×330×550	732×330×555	873×376×555
Dimensiune bruta	Lxlxh	mm	792×393×615	792×393×615	794×376×615	951×431×620
Distanta dintre suportii de prindere		mm				
Greutate neta/ Greutate bruta		kg	25 / 27.5	25 / 27.5	26.5 / 29	36.5 / 39.5
Diametru traseu frigorific	Lichid	inch(mm)	6	6	6	6
	Gaz	inch(mm)	9.52	9.52	9.52	12
Refrigerant			R32	R32	R32	R32

Alimentarea se face la unitatea exterioara