














SPLIT SYSTEMS



-  Refrigerant Leakage Detect
-  Low Ambient Cooling
-  Sweet Dreams
-  Anti-cold Air Function
-  Louvre Position Memory
-  Auto Restart Function
-  24-hour Timer
-  "Diamond-Edged" Casing
-  Emergency Use Function
-  Remote Enable Port
-  Voice Control
-  Smart Home
-  WiFi

A6 DUCT



With its compact design, the Midea A6 Ducted range can be easily mounted in a ceiling void in a commercial office or retail space and offers flexible control and easy maintenance.

FLEXIBLE AIR INTAKE POSITION

Air inlet direction is from rear as standard or can be changed to bottom.

BUILT-IN DRAIN PUMP

The built-in drain pump can lift the condensate water up to 750mm.

MULTI CHANNEL AIR FLOW DISTRIBUTION

The units are suitable for different room types, its multi channel air distribution gives you comfort in every corner.

VERTICAL MOUNTING

Option for vertical mounting of units is available upon request.

LED CHASSIS MOUNTED DISPLAY

Built-in display for easy trouble shooting and system information.

FRESH AIR INLET

Built-in fresh air inlet to create a more comfortable environment.

FLEXIBLE CONTROL AND EASY MAINTENANCE

The electrical control box can be removed away from the unit for easy maintenance access. Standard functional ports are included such as remote On/Off, dry contact switch and alarm signal output.

TWIN COMBINATIONS

Outdoor unit sizes 24, 36, 42, 48 & 55 can be installed with two indoor units for increased flexibility.

REMOTE SIGNAL

Built-in ports for on/off control and fault indication.

SMARTHOME APP

New Wired Controller has built in WiFi, allowing you to operate your system from almost anywhere, at any time.



Indoor unit

Outdoor unit

IR Controller RG10-S (included)

Wired Controller KJR-120M1 (included)




+44 (0) 191 2636367 | mideauk.co.uk | sales@mideauk.co.uk

SPLIT SYSTEMS




BREEZELESS+ CASSETTES, A6 DUCT, CEILING & FLOOR KJR-120M1 - 2-Core Controller



A6 DUCT

INDOOR			MTIU-12HWFNX(GA)	MTIU-18HWFNX(GA)	MTI-24HWFNX(GA)	MTI-36HWFNX(GA)
OUTDOOR			MOX230U-12HFN8-Q(GA)	MOX330U-18HFN8-Q(GA)	MOX430U-24HFN8-Q(GA)	MOD30U-36HFN8-Q(GA)
Nominal Cooling Capacity (min-max)	kW		3.52(0.53-3.99)	5.28(2.55-5.86)	7.03(3.28-8.16)	10.55(2.75-12.02)
Nominal Heating Capacity (min-max)	kW		3.81(1.00-4.39)	5.57(2.20-6.15)	7.62(2.81-8.49)	11.72(2.78-12.78)
UK Total Cooling Capacity	kW		3.79	5.56	7.78	11.38
Seasonal Efficiency SEER / Class	W/W		6.5/A++	6.5/A++	6.2/A++	6.2/A++
Seasonal Efficiency SCOP / Class	W/W		4/A+	4/A+	4/A+	4/A+
Power supply (indoor power via outdoor)	V- Ph-Hz		220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling Current (min-max)	A		4.75(1.3-6.09)	7.1(3.2-9.56)	10.2(4.2-13.2)	17.5(4.2-18.5)
Heating Current (min-max)	A		4.52(1.48-6.15)	6.8(3.3-7.7)	9.2(3.8-11.6)	14.5(3.5-17.5)
Max. input current	A		9	13.5	19	22.5
Recommended Fuse Size (Outdoor)	A		16	16	20	32
Interconnecting/Indoor Power Wiring	No.		4 Core 1mm ²	4 Core 1mm ²	4 Core 1mm ²	4 Core 1mm ²
External Static Pressure	Pa		0-60	0-100	0-160	0-160
Indoor air flow (High - Low)	m ³ /h		600/480/300	911/706.3/515.2	1229/1035/825	2100/1800/1500
Indoor Sound Pressure Level (High-Low)	dB(A)		34.5/30.5/29/23	42/39/35/26	49/46/41/27	50/48/46/42
Indoor unit	Dimensions (WxDxH)	mm	700x506x200	880x674x210	1100x774x249	1360x774x249
	Packing (WxDxH)	mm	860x540x285	1070x725x280	1305x805x315	1570x805x330
	Supply Plenum (WxH)	mm	537x152	706x136	926x175	1186x175
	Return Plenum (WxH)	mm	599x186	782x190	1001x228	1261x228
	Net/Gross Weight	Kg	17.8/21.5	24.4/29.6	32.3/39.1	40.5/48.2
Drainage water pipe diameter	mm		ODØ25	ODØ25	ODØ25	ODØ25
Outdoor air flow	m ³ /h		2200	2100	3500	4000
Outdoor Sound Pressure Level	dB(A)		51	53	57	60
Outdoor unit	Dimensions (WxDxH)	mm	765x303x555	805x330x554	890x342x673	946x410x810
	Packing (WxDxH)	mm	887x337x610	915x370x615	995x398x740	1090x500x885
	Net/Gross Weight	Kg	26.6/29	32.5/35.2	43.9/46.9	66.9/71.5
Refrigerant	Type		R32	R32	R32	R32
	GWP		675	675	675	675
	Charged quantity	Kg	0.72	1.15	1.5	2.4
	Charged to	m	5	5	5	5
	Additional Charge	g/m	12	12	24	24
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ø6.35/Ø9.52(1/4"/3/8")	Ø6.35/Ø12.7(1/4"/1/2")	Ø9.52/Ø15.9(3/8"/5/8")	Ø9.52/Ø15.9(3/8"/5/8")
	Max. pipe length	m	25	30	50	75
	Max. difference in level	m	10	20	25	30
Operating temperature	Indoor (Cooling/Heating)	°C	16-32/0-30	16-32/0-30	16-32/0-30	16-32/0-30
	Outdoor (Cooling/Heating)	°C	-15-50/-15-24	-15-50/-15-25	-15-50/-15-24	-15-50/-15-24

Nominal Conditions: Cooling; indoor 27°C DB, 19°C WB, outdoor 35°C DB, 24°C WB.
 Nominal Conditions: Heating; indoor 20°C DB, outdoor 7°C DB, 6°C WB
 UK Conditions: Summer: indoor 21°C DB, 15°C WB, outdoor 27°C DB. Sound Pressure is measured 1.5m below the air-outlet at Nominal Conditions.



+44 (0) 191 2636367 | mideauk.co.uk | sales@mideauk.co.uk


SPLIT SYSTEMS



A6 DUCT

INDOOR		MTI-42HWFNX(GA)	MTI-48HWFNX(GA)	MTI-36HWFNX(GA)	MTI-48HWFNX(GA)	MTI-55HWFNX(GA)	
OUTDOOR		MOD30U-42HFN8-Q(GA)	MOE30U-48HFN8-Q(GA)	MOD30U-36HFN8-R(GA)	MOE30U-48HFN8-R(GA)	MOE30U-55HFN8-R(GA)	
Nominal Cooling Capacity (min-max)	kW	12.02(2.93-13.7)	14.07(3.52-15.53)	10.55(2.75-12.02)	14.07(3.52-15.53)	15.24 (4.1-18.11)	
Nominal Heating Capacity (min-max)	kW	13.48(3.37-14.07)	16.12(4.10-18.17)	11.72(2.78-12.78)	16.12(4.10-18.17)	18.17(4.40-20.52)	
UK Total Cooling Capacity	kW	12.13	15.54	11.38	15.54	16.89	
Seasonal Efficiency SEER / Class	W/W	6.1/A++	6.1/A++	6.1/A++	6.1/A++	6.1/A++	
Seasonal Efficiency SCOP / Class	W/W	4/A+	4/A+	4/A+	3.8/A+	4/A+	
Power supply (indoor power via outdoor)	V- Ph-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	380-415V, 3Ph, 50Hz	380-415V, 3Ph, 50Hz	380-415V, 3Ph, 50Hz	
Cooling Current (min-max)	A	18.8(3.1-19.8)	21(5.0-26)	6.5(1.4-6.7)	8.4(1.9-10.4)	9.6(3.1-11.5)	
Heating Current (min-max)	A	15.5(3.4-18.3)	22(4.5-26)	5.3(1.3-6.4)	8.0(2.0-9.8)	9.5(2-11.5)	
Max. input current	A	23	29	10	13	14	
Recommended Fuse Size (Outdoor)	A	32	32	16	16	16	
Interconnecting/Indoor Power Wiring	No.	4 Core 1mm2	4 Core 1mm2	4 Core 1mm2	4 Core 1mm2	4 Core 1mm2	
External Static Pressure	Pa	0-160	0-160	0-160	0-160	0-160	
Indoor air flow (High - Low)	m3/h	2400/2040/1680	2400/2040/1680	2100/1800/1500	2400/2040/1680	2600/2210/1820	
Indoor Sound Pressure Level (High-Low)	dB(A)	51.5/49/48/43	51/50/48/43	50/48/46/42	51.5/49/47/42	52.5/49/47	
Indoor unit	Dimensions (WxDxH)	mm	1200x874x300	1200x874x300	1360x774x249	1200x874x300	1200x874x300
	Packing (WxDxH)	mm	1405x915x365	1405x915x365	1570x805x330	1405x915x365	1405x915x365
	Supply Plenum (WxH)	mm	1044x227	1044x227	1186x175	1044x227	1044x227
	Return Plenum (WxH)	mm	1101x280	1101x280	1261x228	1101x280	1101x280
	Net/Gross Weight	Kg	47.6/55.8	47.6/55.8	40.5/48.2	47.6/55.8	47.4/56.1
Drainage water pipe diameter	mm	ODØ25	ODØ25	ODØ25	ODØ25	ODØ25	
Outdoor air flow	m3/h	4000	7500	4000	7500	7500	
Outdoor Sound Pressure Level	dB(A)	60	61	60	61	61	
Outdoor unit	Dimensions (WxDxH)	mm	946x410x810	952x415x1333	946x410x810	952x415x1333	952x415x1333
	Packing (WxDxH)	mm	1090x500x885	1095x495x1480	1090x500x885	1095x495x1480	1095x495x1480
	Net/Gross Weight	Kg	71.0/75.0	91.5/105.4	80.5/85	103.7/118.3	107.0/121.2
Refrigerant	Type		R32	R32	R32	R32	R32
	GWP		675	675	675	675	675
	Charged quantity	Kg	2.8	2.9	2.4	2.9	3
	Charged to	m	5	5	5	5	5
	Additional Charge	g/m	24	24	24	24	24
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Ø9.52/Ø15.9(3/8"/5/8")	Ø9.52/Ø15.9(3/8"/5/8")	Ø9.52/Ø15.9(3/8"/5/8")	Ø9.52/Ø15.9(3/8"/5/8")	Ø9.52/Ø15.9(3/8"/5/8")
	Max. pipe length	m	75	75	75	75	75
	Max. difference in level	m	30	30	30	30	30
Operating temperature	Indoor (Cooling/Heating)	°C	16-32/0-30	16-32/0-30	16-32/0-30	16-32/0-30	16-32/0-30
	Outdoor (Cooling/Heating)	°C	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24

Nominal Conditions: Cooling; indoor 27°C DB, 19°C WB, outdoor 35°C DB, 24°C WB.
 Nominal Conditions: Heating; indoor 20°C DB, outdoor 7°C DB, 6°C WB
 UK Conditions: Summer: indoor 21°C DB, 15°C WB, outdoor 27°C DB. Sound Pressure is measured 1.5m below the air-outlet at Nominal Conditions.



+44 (0) 191 2636367 | mideauk.co.uk | sales@mideauk.co.uk